

# CYBER SERIES

# Cyber SERIES



The Accu-Time Cyber Series is ideal for workforce management applications such as employee time and attendance for payroll, access control, and job tracking. This cost-effective Cyber terminal is a programmable data collection device with features previously reserved for the most expensive platforms. The selectable serial or Ethernet (10/100BASE-T) communications and ATS's Universal Command Set programming interface offer countless configuration options that make the Cyber Series second to none.

- 1 MB RAM option
- 512KB Flash option
- Serial RS232 or RS485
- 10/100BASE-T Ethernet
- Digital bar code wand port
- 33.6K baud modem option
- 802.11b wireless compatible
- Expansion slot for support of plug-in options
- DI/DO port for access control or bell ringing
- Dual proximity readers

Answers for HR Professionals™



To learn more about ATS and the Cyber Series, visit [www.accu-time.com](http://www.accu-time.com) or call 860-870-5000.



## Specifications

- DISPLAY** 4 line x 20 character super twist LCD
- CLOCK** 12 or 24 hour format, USA or international (quartz precision)  
Time stamp of data transactions
- KEYPAD** Software-defined function keys  
Large 20-key tactile 4x5 matrix  
Custom user-defined keypad legends
- MEMORY** Up to 1MB RAM available  
Up to 512k flash memory
- PROGRAMMING** ATS Universal Command Set, C programming language, or  
third-party custom application packages
- SELF-TEST** On-board setup and full-feature diagnostics
- INTERFACE** 802.3 10/100BASE-T Ethernet (optional)  
EIA Standard RS232 or RS485  
Internal modem (optional)  
Optional DI/DO or serial interface printer port
- ENCLOSURE** Die cast aluminum housing with key-lockable base  
Optional gullwing back
- POWER** +10 to +17VDC (12 nominal)  
Optional non-interruptible power source with charger
- ENVIRONMENT** Operation: 32° to 110°F (0° to 43°C)
- PHYSICAL** Size: 7.25" x 7.33" x 4.00" (18.4cm x 18.6cm x 10.2cm)  
Weight: 3.0 lbs. (1.4 kg.)
- CERTIFICATIONS** CE Mark, FCC Part 15 and Part 68
- ACCESSORIES**
- Integrated visible or infrared bar code slot readers
  - Integrated magnetic slot readers
  - Solid state or dry contact relay modules
  - Integrated or external proximity readers
  - Serial interface printer port

## Cyber Series Configuration Guide

Terminal Type	Display	Serial	Ethernet		Modem	Memory	Flash	Mounting	Prox.	DI/DO
			10M	10/100M						
CSS	2x20	---	---	---	Opt.	128K	256K	Gull	---	---
CSE	2x20	Std.	Std.	---	---	128K	256K	Gull	---	---
CSI	4x20	---	---	---	Opt.	512K	256K	Lock	Opt.	Opt.
CS2	4x20	---	---	Std.	Opt.	512K	256K	Lock	Opt.	Opt.
CS3	4x20	---	---	Std.	Opt.	1MB	512K	Lock	Opt.	Opt.

### Accu-Time Systems, Inc.

One Accu-Time Plaza  
Route 83  
Ellington, CT 06029

1-800-355-4648

[www.accu-time.com](http://www.accu-time.com)

TEL: (860) 870-5000

FAX: (860) 872-1511

EMAIL: [sales@accu-time.com](mailto:sales@accu-time.com)

### Accu-Tech Systems Ltd

31 Venture Wales  
Bedwas House  
Business Park  
Caerphilly  
South Wales  
United Kingdom  
CF83 8DW

+44 (0) 2920 885599

[www.accu-tech.co.uk](http://www.accu-tech.co.uk)

**CYBER SERIES**

Connecticut • Chicago • Sarasota • Boston • United Kingdom