Maximus™





The New Maximus[™] - Faster and better than ever!

The new and improved Maximus[™] time clock delivers a straightforward user interface and provides employees the ability to perform fast clock in and clock out transactions.

Accu-Time Systems reengineered the Maximus to outperform its predecessor with a faster processor, greater memory capacity, and a full-color 3.5" screen. The new Maximus is ideal for small businesses or large enterprises that require frequent employee punches. With its back-lit screen and extremely durable keypad, this time clock makes it easier for employees to see and perform accurate employee time tracking transactions..

Maximus[™] features include:

- Eight programmable function keys
- Remote upgradeability
- Biometric option eliminates costly buddy-punching
- Optional power-over-Ethernet module
- Optional GSM modem
- Optional WIFI 802.11 a,b,g,n; WPA2
- DHCP & static IP

To learn more about ATS and Maximus, visit <u>www.accu-time.com</u> or call -1 860.870.5000





Maximus[™] Terminal Specifications

Maximus	Terminal Opecifications	
Display	• 3.5" non-touch transmissive color LCD	THE AMERICAS
Keypad	 20-key tactile 4x5 matrix 	Corporate Headquarters
кеураа		20-B International Drive
	» Numeric keypad 0-9	Windsor, CT 06095
	» Eight software-defined function keys	TEL: (860) 870-5000 FAX: (860) 872-1511
	» Keys, Clear/Enter keys	Toll Free: (800) 355-4648
	Customizable overlay with your brand on the terminal	sales@accu-time.com
Processor	• IMX28 - 454MHZ	www.accu-time.com
Memory	• 512MB NAND FLASH	
Mass Storage	8GB eMMC for CM/Recovery OS Programming	EMEA & APAC
Ethernet	Standard 10/100 BASE-T Ethernet	United Kingdom
	DHCP & Static IP	TEL: +44 (0) 1202 606068
	USB - 2 USB 2.0 Type A Connectors	All Other Locations
Application Software	• OS - Linux	TEL: +44 (0) 2920 885599
	• SDK Java SDK, Java 8, Python	
Platform OS	ATS AccuCollect	
	ATS Universal Command Set (UCS)	
Power	• 5W Average, 12.95W Maximum	
	Optional IEEE 802.3af-compliant Power over Ethernet (PoE)	
Environment	• Operation Temperature: 0° to 50°C (32° to +122°F)	
	• Storage Temperature: -20° to 80°C (-4° to +176°F)	
Dimensions	• 21.33 cm x 22.22 cm x 9.91 cm (8.4" x 8.75" x 3.9")	
Enclosure	Die-cast aluminum housing hinged to key-lockable base	
Certifications	• CE Mark, FCC Part 15 Class A	
Accessories	Biometric readers	
	Digital Persona	
	Optical and Capacitive Suprema, Lumidigm	ATS
	 Smartcard readers – contactless (HID[®] Prox, Mifare[™], iClass[®]) 	
	Optional external reader - Wiegand compatible & USB	
	• WIFI 802.11 a,b,g,n; WPA2	



ACCU-TIME SYSTEMS INC.

To learn more about ATS, visit www.accu-time.com or call: 1 (800) 355-4648. As part of Accu-Time's continuous improvement process, we reserve the right to change product specifications without notice (0321).