



stride80® Purpose-built to ignite growth!

Accu-Time Systems' new stride80® was built to ignite growth. Whether you are leveraging the stride80 to easily and seamlessly integrate an existing Android application or developing new and interactive employee self-service applications, the stride80 brings a new competitive edge to your business; opening the door to new markets.

With our comprehensive Software Development Kit (SDK) to guide you, you'll be able to quickly deploy your most innovative employee self-service applications; and if you ever need it, our customer support team is here to provide expert support.

stride80® features include:

- Android-based
- 8" Widescreen Touch Display
- Speakers
- Microphone
- eMMC – 16GB Storage

To learn more about ATS and stride80,
visit www.accu-time.com or
call -1 860.870.5000



stride80® Terminal Specifications

Operating System	<ul style="list-style-type: none">• Android 8.1• Software Development Kit available	ACCU-TIME SYSTEMS INC. THE AMERICAS Corporate Headquarters 20-B International Drive Windsor, CT 06095 TEL: (860) 870-5000 FAX: (860) 872-1511 Toll Free: (800) 355-4648 sales@accu-time.com www.accu-time.com
User Interface	<ul style="list-style-type: none">• 8" Capacitive multi-touch color screen• Software controllable multicolor LED indicator bar• Microphone and speaker• Presence sensor• LED indicator for camera usage• Optional - - 8 Mega Pixel Camera - Supports photo and video• Optional - - Keypad - 20 keys 0-9 , F1-F6, Clear and Enter keys	
Memory	<ul style="list-style-type: none">• 2GB	
Mass Storage	<ul style="list-style-type: none">• 16GB of which 5GB are user available	
Central Processing Unit (CPU)	<ul style="list-style-type: none">• Quad Core A7, 1.1GHz	EMEA & APAC United Kingdom TEL: +44 (0) 1202 606068
Communications	<ul style="list-style-type: none">• 10/100 Mbps, Ethernet with DHCP, Static IP address• Optional - 4G GSM Modem• WIFI - 2.4Gbit/s, 802.11 b/g/n• Base Model:<ul style="list-style-type: none">» 8.98" wide x 7.69" high x 3.13" deep» 228.2mm wide x 195.3mm high x 79.6mm deep• XL Model:<ul style="list-style-type: none">» 12.17" wide x 7.69" high x 3.13" deep» 309.0mm wide x 195.3mm high x 79.6mm deep• Mag swipe add on<ul style="list-style-type: none">» 1.16" x 3.74" x 1.34"» 29.47mm x 96mm x 34.04mm	
Dimensions		All Other Locations TEL: +44 (0) 2920 885599
Power	<ul style="list-style-type: none">• 12V DC 30W output Terminal power consumption less than 30 Watts• Optional - PoE IEEE 802.3at (30W, PoE+)• Optional - - Battery - Li-ion 8.4v @ 2600 mAh up to 1 hr of operation.	
Environment	<ul style="list-style-type: none">• Operating Temperature: 0° to 50°C (32° to 122°F)	
Supported readers and card technologies	<ul style="list-style-type: none">• Optional - Barcode scanner Visible red light• Optional - Biometric readers<ul style="list-style-type: none">» Lumidigm 1:N 1,300 & 1:1 50,000 templates» Suprema USB capacitive & optical» 1:N 5000 & 1:1 50,000 templates• Optional - Proximity readers - HID Prox, iClass SE, Fare and Marin• Optional - Mag stripe reader - Track 1, 2, 3	

